## **©OUTLANDER™ MAX PRO 650 T3B**

## **HIGHLIGHTS**

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with Extra Low L gear
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN† winch with roller fairlead
- Torsional Trailing arm Independent rear suspension (TTI)
- Increased ground clearance
- · Reinforced seat skin
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle† ACT HD radial tires
- · Relocated air intakes

- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards
- 21.4 L (5.6 gal.) water-resistant rear compartment



Brushed Aluminum / 650

ENGINES	650
Туре	62 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Maximum Speed	60km/h
CHODENCIONO	

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm (9 in.) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6cm (9.3-in) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
ABS	N/A

TIRES / WHEELS	
Front Tires	Carlisle† ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES				
LxWxH	238.8 x 116.8 x 135 cm (94 x 46 x 53.2 in.)			
Wheelbase	149.9 cm (59 in.)			
Ground Clearance	30.5 cm (12 in.)			
Seat Height	87.7 cm (34.5 in.)			
Dry Weight*	372 kg			
Rack Capacity	Front: 45 kg Rear: 90 kg			
Storage Capacity	Rear: 21.4 L			
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes			
Fuel Capacity	20.5 L			

<b>FEATURES</b>				
Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation Lighter type DC outlet in console, standard in the back (15-A)		
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light	
		Seat	Convertible Rack System (CRS) with reinforced seat skin	
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)	
T3B features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Protection	N/A	

W				

Factory 2 years

©2017 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. \*Visco-Lok is a trademark of GRN Viscodrive GmbH. \*All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. BRP highly recommends that all All Vidrivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the All Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.





Can-AmOffroad.com