

2018 OUTLANDER™ XT 650 T3B ABS

HIGHLIGHTS

- Rotax® V-twin engine
- Anti-Lock Braking System (ABS)
- Continuously Variable Transmission (CVT)
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- Painted plastics for premium look
- 14-in. cast-aluminum wheels
- 26-in. ITP† Terracross radial tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent (TTI) rear suspension
- 625-W magneto
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 21.4 L (5.7 gal.) water-resistant rear compartment



Intense red / 650

ENGINES

650

Type	62 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Maximum Speed	105km/h

SUSPENSIONS

Front Suspension	Double A-arm 22.9 cm (9 in.) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6 cm (9.3 in.) travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
ABS	Standard

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
T3B features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Seat	Standard
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
		Protection	Heavy-duty front & rear bumpers, wind deflectors

TIRES / WHEELS

Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 8 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. aluminum

DIMENSIONS / CAPACITIES

L x W x H	218.4 x 116.8 x 126 cm (86 x 46 x 49.5 in.)
Wheelbase	129.5 cm (51 in.)
Ground Clearance	27.9 cm (11 in.)
Seat Height	87.7 cm (34.5 in.)
Dry Weight*	329 kg
Rack Capacity	Front: 45 kg Rear: 90 kg
Storage Capacity	21.4L
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	20.5L

WARRANTY

Factory	2 years
---------	---------

BEST ©2017 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. **ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain.** ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am



Can-AmOffroad.com